# Installs in Seconds & Virtually Vanishes

By far the smallest wireless door/window contact currently available in the world, the wafer-thin profile of the EV-DW4975 provides a streamlined, practically non-existent look once installed. The contact can be easily mounted to a window frame with double-sided tape, eliminating the need for drilling. This not only reduces installation times but also retains the integrity of window warranties. A generous magnet gap of 5/8" (16 mm) easily accommodates larger door or window frames. The EV-DW4975 is built with reliable 433 MHz technology and is compatible with all current DSC wireless receivers.







#### **Product Features:**

- Wafer-thin profile
- ► Long-life lithium battery included
- ▶ 5/8" (16 mm) maximum magnet gap
- Double-sided tape (included)
- Smooth-back plastics
- Reliable 433 MHz technology
- ► FCC/IC listed



### Value Added

Significantly smaller than competitor door/window contacts, the EV-DW4975 is housed within a compact casing that allows it to be used for the tightest-fitting installations. Once installed, the contact is inconspicuous and complements the décor of most homes. It is built with reliable 433 MHz technology, uses a long-life lithium battery and is compatible with all current DSC wireless receivers.

Ordering Information:		
EV-DW4975		
	(NA Baud Rate)	

## **Compatibility**

The EV-DW4975 is compatible with the following receivers:

PowerSeries™ Wireless Receivers RF5132-433/PC5132-433 all versions and RF5108-433

MAXSYS® Wireless Receiver PC4164-433

PowerSeries RFK Keypads (RFK5500/RFK5501/RFK5516/RFK5508)

Fixed-Message LCD Keypad with Integrated Wireless Receiver RF5501-433

Envoy™ LCD Self-Contained Wireless Security System NT9005

# **Specifications**

Dimensions	. 2 <sup>1/4</sup> " x 1" x 3/16"
	(57 mm x 25.4 mm x 4.8 mm)
Battery	. CR2032 (3 V Lithium)
Battery Life	. 5-8 Years (Typical)
Operating Temperature	10 to 50 °C (14-122 °F)
Operating Humidity	. 5-93% RH